

















## سیپارات

ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
<b>IP Camera - IR</b>				
1	<b>SM-IP8414M-W</b> 	1/2.8" <b>SONY CMOS Sensor 8MP(20FPS)/3.6 mm fixed Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.1 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions</b>	 WDR	122,887,500
2	<b>SM-IP4512HM-W</b>	1/3" CMOS Sensor <b>4MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120DB /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions</b>	 WDR	49,437,500
3	<b>SM-IP2412HM-WS</b>	1/2.8" CMOS Sensor <b>2MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB/ ONVIF/IP67 Metal SMART Functions</b>	 WDR Starlight	46,047,500
4	<b>SM-IP2512HM-WS</b>	1/2.8" CMOS Sensor <b>2MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions</b>	 WDR Starlight	46,047,500
5	<b>SM-IPTZ-4MP-40X/MSFD</b>	1/2.8" progressive scan CMOS Sensor, BSI and NIR++,dual gain, <b>4MP(25FPS) 4.5 ~ 180 mm Motorized Lens/40x Optical Zoom/350m Smart IR/H.265+,H.264+/ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC24V 2.5A ,PoE+ SMART Functions/ Auto Tracking/ Supports face detection/ target counting</b>	 WDR Starlight Auto Tracking	5inch 661,050,000
6	<b>SM-IPTZ-4MP-4X/MWSFR</b>	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor <b>4MP(25FPS) 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+/ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics &amp;Speaker (8m for voice recording, 30m for audible warnings ) / 1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Supports face detection and comparison/ Active Deterrence (30m White LED)</b>	 Auto Tracking WDR Starlight	3inch 210,180,000
7	<b>SM-IPTZ-4MP-4X/MWS</b>	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor <b>4MP(25FPS) 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+/ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics &amp;Speaker (8m for voice recording, 30m for audible warnings ) / 1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Active Deterrence (30m White LED)</b>	 WDR Starlight	3inch 180,800,000






















8	<b>SM-IPTZ-2MP-15X/MS</b>	1/2.8" progressive scan CMOS, BSI, NIR++/ <b>2MP(25FPS)</b> 5 ~ 75 mm Motorized Lens/ <b>15x Optical Zoom</b> /200m SMART IR/ <b>H.265+,H.264+/DWDR /Starlight</b> SD Card Max <b>256GB</b> /IP66, IK10 Metal /DC12V 3A, ,PoE SMART Functions/ Auto Tracking	  4inch	257,075,000
---	---------------------------	--	--	-------------








































**Light Explorer** IP Camera - Color View

9	<b>SM-IP2414CV2-W</b>	1/2.8" CMOS Sensor <b>2MP(25FPS)</b> / 3.6mm & 2.8 mm fixed Lens/3Streams/ <b>H265+/ H264+</b> <b>True WDR 120dB</b> /30~ 40m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ <b>1CH audio input; 1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/IP67 Metal SMART Functions	  	60,737,500
10	<b>SM-IP2512CV2-W</b>	1/2.8" CMOS Sensor <b>2MP(25FPS)</b> / 2.8 mm fixed Lens/3Streams/ <b>H265+ H264+</b> <b>True WDR 120dB</b> /20~ 30m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ <b>1CH audio input; 1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/IP67 Metal SMART Functions	  	53,675,000



















IP Camera - Dual Light

11	<b>NEW</b> <b>SM-IPN8512DM-W</b>	1/2.8" <b>SONY</b> CMOS Sensor <b>8MP(20FPS)</b> /2.8mm fixed Lens/3Streams/ <b>H265+/H264+</b> <b>True WDR 120dB</b> /0.02 lux/ ICR , Auto day/night switch 30m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog, ANR, Cloud upgrade, Dual-system backup POE/12VDC/ <b>1CH audio input/1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/ <b>IP67</b> (Metal) SMART Functions-Support <b>SMD</b> (human / Motor Vehicle)	   	128,255,000
12	<b>NEW</b> <b>SM-IPN6416DM-ZWS</b>	1/2.5" CMOS Sensor <b>6MP(20FPS)</b> /2.8 -12mm <b>Motorized</b> Lens/3Streams/ <b>H265+/H264+</b> <b>True WDR 120dB/Starlight</b> /0.008 lux/ ICR , Auto day/night switch 40m <b>White light</b> view distance; 50m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/ <b>1CH audio input/1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/ <b>IP67</b> (Metal) SMART Functions-Support <b>SMD</b> (human / Motor Vehicle)	   	136,730,000
13	<b>SM-IPN6412DM-WS</b>	1/2.5" CMOS Sensor <b>6MP(20FPS)</b> /3.6mm fixed Lens/3Streams/ <b>H265+/H264+</b> <b>True WDR 120dB/Starlight</b> /0.008 Lux/ ICR , Auto day/night switch 30m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/ <b>1CH audio input/1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/ <b>IP67</b> (Metal) SMART Functions-Support <b>SMD</b> (human / Motor Vehicle)	   	84,750,000
14	<b>SM-IPN6512DM-WS</b>	1/2.5" CMOS Sensor <b>6MP(20FPS)</b> /2.8mm fixed Lens/3Streams/ <b>H265+/H264+</b> <b>True WDR 120dB/Starlight</b> /0.008 Lux/ ICR , Auto day/night switch 30m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/ <b>1CH audio input/1CH built-in MIC</b> /SD Card Max <b>256GB</b> /ONVIF/ <b>IP67</b> (Metal) SMART Functions-Support <b>SMD</b> (human / Motor Vehicle)	   	84,750,000
15	<b>SM-IPN4410DL</b>	1/3" CMOS Sensor <b>4MP(25FPS)</b> /3.6mm fixed Lens/2Streams/ <b>H265+/H264+</b> DWDR /0.09 Lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ <b>1CH built-in MIC</b> /ONVIF/ <b>IP67</b> (Metal&Plastic) SMART Functions-Support <b>SMD</b> (available for human)	   	43,505,000



16	SM-IPN4510DL	1/3" CMOS Sensor <b>4MP(25FPS)/2.8mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR /0.09 Lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal&Plastic) <b>SMART Functions-Support SMD (available for human)</b>	   	43,505,000
17	SM-IPN2416DM-VFWS	1/2.8" CMOS Sensor <b>2MP(25FPS)/2.8 -12mm</b> Varifocal Lens/3Streams/H265+/H264+/ <b>True WDR 120dB/Starlight</b> /0.006 Lux/ ICR , Auto day/night switch 40m <b>White light</b> view distance; 50m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, cloud upgrade POE/12VDC/1 <b>CH audio Input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67</b> (Metal) <b>SMART Functions-Support SMD (human / Motor Vehicle)</b>	    	70,625,000
18	SM-IPN2516DM-VFWS	1/2.8" CMOS Sensor <b>2MP(25FPS)/2.8 -12mm</b> Varifocal Lens/3Streams/H265+/H264+/ <b>True WDR 120dB/Starlight</b> /0.006 Lux/ ICR , Auto day/night switch 40m <b>White light</b> view distance; 50m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, cloud upgrade POE/12VDC/1 <b>CH audio Input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67</b> (Metal) <b>SMART Functions-Support SMD (human / Motor Vehicle)</b>	    	70,625,000
19	NEW SM-IPN2412DL	1/3" CMOS Sensor <b>2MP(25FPS)/3.6mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR/0.02 lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal) <b>SMART Functions-Support SMD ( available for human )</b>	   	39,267,500
20	SM-IPN2410DL	1/3" CMOS Sensor <b>2MP(25FPS)/3.6mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR/0.02 Lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal&Plastic) <b>SMART Functions-Support SMD (available for human)</b>	   	36,160,000
21	NEW SM-IPN2512DL	1/3" CMOS Sensor <b>2MP(25FPS)/2.8mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR /0.02 lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal) <b>SMART Functions-Support SMD ( available for human )</b>	   	39,267,500
22	SM-IPN2510DL	1/3" CMOS Sensor <b>2MP(25FPS)/2.8mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR /0.02 Lux/ ICR , Auto day/night switch 20m <b>White light</b> view distance; 30m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal&Plastic) <b>SMART Functions-Support SMD (available for human)</b>	   	36,160,000
23	SM-IPS2410DL	1/3" CMOS Sensor <b>2MP(25FPS)/3.6mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR/0.0462 Lux/ ICR , Auto day/night switch <b>Dual light Camera (line Crossing-Intrusion)</b> 20m <b>White light</b> view distance; 20m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC,Defog POE/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal&Plastic) <b>SMART Functions</b>	  	26,272,500
24	SM-IPS2510DL	1/3" CMOS Sensor <b>2MP(25FPS)/2.8mm</b> fixed Lens/2Streams/H265+/H264+/ DWDR/0.0462 Lux/ ICR , Auto day/night switch <b>Dual light Camera (line Crossing-Intrusion)</b> 20m <b>White light</b> view distance; 20m <b>IR</b> view distance ROI coding, AWB, 3D DNR, HLC, BLC,Defog POE/1 <b>CH built-in MIC/ONVIF/IP67</b> (Metal&Plastic) <b>SMART Functions</b>	  	26,272,500
<b>NVR</b>				
25	SM-NLS4016	4CH input & Record <b>6MP@25fps /H.265S ,H.265+/</b> Bandwidth(Input 40Mbps/Output 40Mbps) 4CH IPC Audio/Alarm Input/SATA3.0 × 1 , max <b>10T /</b> HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps × 1 <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection</b> قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	40,962,500










26	<b>SM-NLS4016-4PE</b>	<p>4CH input &amp; Record <b>6MP@25fps</b> - 4*100M RJ45 PoE ports  <b>H.265S ,H.265+</b> -Bandwidth(Input 40Mbps/Output 40Mbps)  4CH IPC Audio input/SATA3.0 × 1, max 10T /  HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/  RJ45 100Mbps × 1  <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>63,280,000</b>
27	<b>SM-NLS8016</b>	<p>8CH input &amp; Record <b>6MP@25fps /H.265S ,H.265+/</b>  Bandwidth(Input 64Mbps/Output 64Mbps)  8CH IPC Audio/Alarm input/SATA3.0 × 1, max 10T /  HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/  RJ45 100Mbps × 1  <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>47,460,000</b>
28	<b>SM-NLS1616</b>	<p>16CH input &amp; Record <b>6MP@25fps /H.265S ,H.265+/</b>  Bandwidth(Input 64Mbps/Output 64Mbps)  16CH IPC Audio/Alarm input/SATA3.0 × 1, max 10T /  HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/  RJ45 100Mbps × 1  <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>53,675,000</b>
29	<b>SM-N2M818</b>	<p><b>NEW</b>  8CH input &amp; Record <b>8MP(25FPS)/H.265S ,H.265+</b>  Bandwidth (Input80Mbps/Output 80Mbps)  8CH IPC Audio/Alarm input/SATA3.0 × 1, max 10T/  <b>HDMI 4K-VGA/ 2 RCA AUDIO IN &amp; OUT/</b>  USB2.0*2 /P2P/ONVIF/DHCP/DDNS  RJ45 10-100-1000M  <b>SMART Function/ Supports face detection/Video Metadata/ Perimeter Protection/ Support fisheye (Web Client and mobile APP)</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>84,185,000</b>
30	<b>SM-N2M1618</b>	<p>16CH input &amp; Record <b>8MP(25FPS)/H.265S ,H.265+/</b>  Bandwidth (Input160Mbps/Output 160Mbps)  16CH IPC Audio/Alarm input/SATA3.0 × 1, max 10T/  <b>HDMI 4K-VGA/ 2 RCA AUDIO IN &amp; OUT/</b>  USB2.0*2 /P2P/ONVIF/DHCP/DDNS/  RJ45 10-100-1000M  <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP)</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>88,705,000</b>
31	<b>SM-N2M1628</b>	<p>16CH input &amp; Record <b>8MP(25FPS)/H.265S ,H.265+/</b>  Bandwidth (Input160Mbps/Output 160Mbps)  16CH IPC Audio/Alarm input/4 CH local alarm input- 1Ch  Output/SATA3.0 × 2, max 10T per HDD/HDMI 4K-VGA  2 RCA AUDIO IN &amp; OUT/RS485*2/  USB2.0*2 /P2P/ONVIF/DHCP/DDNS/  RJ45 10-100-1000M  <b>SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP)</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 	<b>112,435,000</b>
32	<b>SM-N2H32212-AI</b>	<p><b>NEW</b>  32CH input &amp; Record <b>12MP(20FPS)/ H.265S/H.265+/H264/</b>  Bandwidth(Input 320Mbps/Output 256Mbps)  32CH IPC Audio input/8Ch local Alarm input - 4Ch  Output/2HDD*10TB  HDMI*2(4K &amp; 1080P)-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/  USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS  RJ45 10-100-1000M * 2  <b>AI Function-Supports face detection and comparison (32CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (NVR/ Web Client and mobile APP)</b>  قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	     	<b>211,875,000</b>









کلیه محصولات لیست با گارانتی شرکت سیماران می باشند

## سیماران


## Simaran Project Series

ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
<b>IP Camera - IR</b>				
1	SM-IP8416M-WZ 	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8 -12mm Motorized Varifocal Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.05 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions	 WDR	Hyperlink Call
2	NEW SM-IPN8416M-ZW	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8 -12mm Motorized Varifocal Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.02 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions	 WDR	Hyperlink Call
3	SM-IPN6412H-WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	 WDR Starlight Metadata SMD	Hyperlink Call
4	NEW SM-IPN6514H-WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/1CH alarm input; 1CH alarm output/SD Card Max 256GB/ONVIF/IP67 & Ik10 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	 WDR Starlight Metadata SMD	Hyperlink Call
5	SM-IPN6512H-WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	 WDR Starlight Metadata SMD	Hyperlink Call
6	SM-IP4412H-WMFD	1/3" CMOS Sensor 4MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /HFR(MAX 60fps in 1080p)/30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR POE/12VDC/1CH Audio Input/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata	 WDR Metadata	Hyperlink Call




7	<p><b>SM-IP4512H-WMFD</b></p>	<p>1/3" CMOS Sensor <b>4MP(25FPS)/2.8 mm</b> fixed Lens/3Streams/H265+/H264+  <b>True WDR 120dB /HFR(MAX 60fps in 1080p)/30m IR/0.005 Lux/ICR auto switch, true day / night</b>  <b>ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR</b>  <b>POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal</b>  <b>SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata</b></p>		<p>Hyperlink</p> <p><b>Call</b></p>
8	<p><b>SM-IP2416HZ-WSLR 7-22mm</b></p> 	<p><b>2MP ANPR Network Camera; Speed: up to 70 KM/H</b>  <b>1/2.8" SONY CMOS Sensor</b>  <b>2MP(25FPS) / 1080P 60fps in HFR mode</b>  <b>7-22mm Motorized Varifocal Lens</b>  <b>3Streams/Smart coding H.265S/H.264S/H265+/H264+</b>  <b>True WDR 120dB/Starlight/100m IR /0.005 Lux, ICR auto switch, true day/night</b>  <b>ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR</b>  <b>POE/12VDC/ 1CH audio input; 1CH audio output/ 1CH alarm input; 1CH alarm output /SD Card Max 256GB/ CVBS output/RS485/Wiegand/ONVIF/IP67 Metal</b>  <b>SMART Functions- Supports license plate recognition</b>  <b>LPR Distance: 4 ~ 17m</b></p>		<p>Hyperlink</p> <p><b>Call</b></p>
9	<p><b>SM-IPTZ-4MP-37X/HSFR</b></p> 	<p><b>1/1.8" progressive scan CMOS Sensor 4MP(25FPS)/ 5.6 ~ 208 mm Motorized Lens/37x Optical Zoom/500m VCSEL IR/H.265,H.264/DWDR/Starlight</b>  <b>1 Ch input, 1 Ch output Audio/7 Ch input ,2 Ch output Alarm/SD Card Max 256GB/CVBS Analog Output/RS485/ IP67, IK10 Metal/Outdoor/ AC24V 5A, DC24V,PoE++</b>  <b>SMART Functions/ Auto Tracking/ Supports face detection and comparison/ Target counting</b></p>	 <p>8inch</p>	<p>Hyperlink</p> <p><b>Call</b></p>
10	<p><b>SM-IPTZ-4MP-25X/MWSFR</b></p>	<p><b>1/2.7" progressive scan CMOS, BSI, NIR+/ 4MP(25FPS)/ 4.8 ~ 120 mm Motorized Lens/25x Optical Zoom/160m SMART IR/H.265+,H.264+/True WDR 120dB/Starlight</b>  <b>1 Ch input, 1 Ch output Audio/1CH Alarm input; 1CH Alarm output/SD Card Max 256GB/IP66, IK10 Metal /DC12V 3A, ,PoE+</b>  <b>SMART Functions/ Auto Tracking/ Supports face detection and recognition/ Target counting</b></p>	 <p>4inch</p>	<p>Hyperlink</p> <p><b>Call</b></p>
11	<p><b>SM-IP842PH-SFR</b></p> 	<p><b>8MP 180° Panoramic Network Camera</b>  <b>1/2.8" SONY(4pcs*2MP) progressive scan CMOS Sensor / 8MP(4096 × 1800) (25FPS)</b>  <b>3.2mm fixed Lens x 4 /3Streams/H.265+/H.264+ DWDR/ Starlight/ 20m IR/ 0.008 lux/ 12V DC/ PoE/ ONVIF</b>  <b>1/1 CH Audio In/Output , 1/1 CH Alarm In/Output, SD Card Max 256GB, RS485</b>  <b>3D DNR, HLC, BLC, defog, EIS, IP67, IK10</b>  <b>SMART Functions / Supports face detection and comparison</b></p>	 <p>Panoramic Image</p>	<p>Hyperlink</p> <p><b>Call</b></p>
12	<p><b>SM-IPS27MFP</b></p>	<p><b>Face Panel &amp; Access Control Terminal</b>  <b>Standalone/7 inch LCD screen/Face Liveness Detection</b>  <b>1/2.8" progressive scan CMOS Sensor/ 2MP(25FPS)</b>  <b>4.3 mm x 2 lens/3Streams/H265+/H264+/ WDR(72dB), 3D DNR, HLC, BLC, defog, DC12V/1A</b>  <b>Face Recognition Distance: 1.5m</b>  <b>Face Picture Database: 10,000</b>  <b>White Light Distance: 1m soft light</b>  <b>IR Light Distance: 2m</b>  <b>1 Built-in MIC/Built-in Speaker - 1/1 CH Alarm In/Output</b>  <b>1CH RJ45-1CH Wiegand-1CH Lock-1CH Door contact input-Exit Buttonx1-Tamper Buttonx1-Built-in card reader</b>  <b>door opening modes (Only card, Only face recognition, card and face recognition, card Or face recognition)</b>  <b>Card Type: Mifare Card/Desfire Card/FM1208 Card/Gicard</b>  <b>SMART Functions /Supports face detection and comparison</b></p>		<p>Hyperlink</p> <p><b>Call</b></p>





13	<p><b>SM-IP2PhS-WFD</b></p>	<p>2MP Pinhole Camera            1/2.8" <b>SONY</b> Progressive Scan CMOS <b>2MP(25FPS)/2.8 mm</b>            fixed Lens/3Stream/<b>H.265+/H.264+</b>  <b>True WDR 120dB (HD camera) /0.05 Lux</b>            ROI coding, 3D DNR, HLC, BLC, defog  <b>POE/12VDC, 1/1 CH Audio In/Output, 8/4 CH Alarm In/Output,</b>  <b>1CH BNC video input connector, SD Card Max 256GB /ONVIF/</b>  <b>Support UTC control</b>  <b>SMART Functions/Perimeter protection/Supports Face</b>  <b>detection and face capture/ target counting</b></p>	<p>HD camera + Converter</p>  <p>WDR</p>	<p>Hyperlink</p> <p>Call</p>
----	-----------------------------	--	---	------------------------------


**Light Explorer** IP Camera - Color View

14	<p><b>SM-IP4418CV2-W</b></p>	<p>1/3" CMOS Sensor <b>4MP(25FPS)/ 6mm</b> fixed            Lens/3Streams/<b>H265/ H264/</b>  <b>True WDR 120dB/30~ 40m</b> white light view distance/0.003 lux            ROI coding, AWB, 3D DNR, HLC, BLC  <b>POE/12VDC/1CH audio input; 1CH built-in MIC /SD Card Max</b>  <b>256GB/ ONVIF/IP67(Metal&amp;Plastic)</b>  <b>SMART Functions</b></p>	<p>Full-Color WDR</p> 	<p>Hyperlink</p> <p>Call</p>
----	------------------------------	--	---	------------------------------





















**NVR**

15	<p><b>NEW</b></p> <p><b>SM-N2H8116-AI</b></p>	<p>8CH input &amp; Record <b>16MP(25FPS)/ H.265S/H.265+/H264/</b>            Bandwidth(Input 160Mbps/Output 160Mbps)            8CH IPC Audio input/8Ch local Alarm input - 4Ch  <b>Output/1HDD*10TB</b>  <b>4K HDMI-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/</b>  <b>USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/</b>  <b>RJ45 10-100-1000M *2</b>  <b>AI Function- Supports face detection and comparison (8CH -</b>  <b>AI by IPC / 2CH (2MP) - AI by Device) / License plate</b>  <b>recognition/ Video Metadata/ Supports fisheye camera access</b>  <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	<p>Deep Learning Algorithm VCA Face Recognition</p>  <p>License plate recognition Metadata Fisheye</p>	<p>Hyperlink</p> <p>Call</p>
----	---	--	---	------------------------------

16	<p><b>NEW</b></p> <p><b>SM-N2H16216-AI</b></p>	<p>16CH input &amp; Record <b>16MP(25FPS)/ H.265S/H.265+/H264/</b>            Bandwidth(Input 192Mbps/Output 192Mbps)            16CH IPC Audio input/8Ch local Alarm input - 4Ch  <b>Output/2HDD*10TB</b>  <b>4K HDMI-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/</b>  <b>USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/</b>  <b>RJ45 10-100-1000M *2</b>  <b>AI Function- Supports face detection and comparison (16CH -</b>  <b>AI by IPC / 2CH (2MP) - AI by Device) / License plate</b>  <b>recognition/ Video Metadata/ Supports fisheye camera access</b>  <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	<p>Deep Learning Algorithm VCA Face Recognition</p>  <p>License plate recognition Metadata Fisheye</p>	<p>Hyperlink</p> <p>Call</p>
----	--	---	---	------------------------------

17	<p><b>SM-NH32212-AI</b></p>	<p>32CH input &amp; Record <b>12MP(25FPS)/ H.265S/H.265+/H265/</b>            Bandwidth(Input 192Mbps/Output 192Mbps)            32CH IPC Audio input/8Ch local Alarm input - 4Ch  <b>Output/2HDD*10TB</b>  <b>HDMI*2(4K &amp; 1080P)-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/</b>  <b>USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/</b>  <b>RJ45 10-100-1000M * 2</b>  <b>AI Function-Supports face detection and comparison (32CH -</b>  <b>AI by IPC / 2CH (2MP) - AI by Device) / License plate</b>  <b>recognition/ Video Metadata/Support fisheye (Web Client and</b>  <b>mobile APP)</b>  <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	<p>Deep Learning Algorithm VCA Face Recognition</p>  <p>License plate recognition Metadata</p>	<p>Hyperlink</p> <p>Call</p>
----	-----------------------------	--	---	------------------------------



18	SM-N2H32412-AI	<p>32CH input &amp; Record <b>12MP(20fps), 9MP or lower(25fps)</b>  <b>H.265S/H.265+/H265/</b>          Bandwidth(Input 320Mbps/Output 256Mbps)          32CH IPC Audio input/16Ch local Alarm input - 4Ch          Output/4HDD*10TB/eSATA*1/          HDMI*2(4K &amp; 1080P)-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/          USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/          RJ45 10-100-1000M * 2  <b>AI Function-Supports face detection and comparison (32CH - AI by IPC / 2CH - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (Web Client and mobile APP)</b>          قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	     	<p>Hyperlink</p> <p>Call</p>
19	SM-NH32812-AI	<p>32CH input &amp; Record <b>12MP@20fps; 8MP or lower@25fps/</b>  <b>H.265S/H.265+/H265/</b>          Bandwidth(Input 320Mbps/Output 320Mbps)          32CH IPC Audio input/16Ch local Alarm input - 4Ch          Output/8HDD*10TB/eSATA*1          HDMI*2(4K &amp; 1080P)-VGA/2 RCA AUDIO IN &amp; OUT/RS485*2/Supports RAID0, RAID1, RAID5, RAID6, RAID10          USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/          RJ45 10-100-1000M * 2  <b>AI Function- Supports face detection and comparison (32CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (Web Client and mobile APP)</b>          قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	      	<p>Hyperlink</p> <p>Call</p>
20	SM-NH64816-AI	<p>64CH input &amp; Record <b>16MP@25fps</b>  <b>H.265S/H.265+/H265/</b>          Bandwidth(Input 640Mbps/Output 640Mbps)          64CH IPC Audio input/ 8HDD*10TB/eSATA*2          HDMI*4(8k &amp; 4K &amp; 1080P)-VGA/2 RCA AUDIO IN &amp; OUT/16Ch local Alarm input - 4Ch Output//RS485*2/Supports RAID0, RAID1, RAID5, RAID6, RAID10          USB2.0*2 &amp; USB3.0*1/P2P/ONVIF/DHCP/DDNS/          RJ45 10-100-1000M * 2  <b>AI Function- Supports face detection and comparison (64CH - AI by IPC / 4CH - AI by Device) / License plate recognition/ Video Metadata/ Fisheye</b>          قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	      	<p>Hyperlink</p> <p>Call</p>

کلیه محصولات لیست با 38 ماه گارانتی شرکت سپاران می باشند